

### Product Definition

BILIZO® FLOOR MMA SELF is an acrylate binder based, two component, special floor coating.

### Application Areas

It is used in the production of all kinds of markings for coating, warning and information purposes on asphalt or concrete floors.

### Advantages

is a professional use coating that is used with the help of special application apparatus, toothed trowels and machines, makes it dry quickly, has excellent abrasion resistance and adhesion to surfaces.

### Package

It consists of 20 kg component A and 0,20 kg component B (hardener).

### Technical Data

Connector Type	Acrylate Resin
Viscosity (25°C)	100-110
Density (g/ml)	1.75 ± 0.01
Solids (% by Weight)	80 ± 5
Gloss (60°)	Mat
Flash Point (°C)	>35
Storage Stability	min. 4 points
Theoretical Spread Rate	1-1.2 m <sup>2</sup> /liter (1900µ dry film thickness)
Mixing Ratio	100/1
Drying Time (23°C, 50%RR)	Touch Dry : 15-20 minutes

### Application

#### Surface Preparation:

The most important factor affecting the performance of the coating on the applied surface is the surface preparation. The reason for making surface preparation before paint applications is to ensure that the paints adhere to the applied surface in the most effective way. Surface preparation processes should serve the purpose of making the coating part of the surface rather than obtaining it as a thin layer on the surface.

#### Method of Application:

Application is made with the help of application apparatus and machines. I. and II. components are mixed in the specified ratio and the application is made.

#### Important Notices:

Before using the coating, it should be mixed thoroughly by paying attention to the mixing ratio. During the application, the ambient temperature should be 5-35°C. After each application; application tools should be cleaned with cellulosic thinner. The surfaces on which BILIZO flooring is applied should be protected from physical and chemical factors for 1/2 hour. Paint should never be discharged into sewers and water channels. The application should be done as stated above. After partial use; The mouth of the package should be tightly closed.

### Storage

It can be stored for one year in its unopened original packaging, in an environment of 5-35°C, out of direct sunlight. It should be protected from extreme temperature and humidity.

### Safety Information

This paint is purely for professional users. Easily flammable. Harmful by inhalation, in contact with skin and if swallowed. Keep out of reach of children. Keep the box tightly closed, in a cool and well-ventilated place. Keep away from ignition sources, do not smoke. Avoid eye and skin contact. Do not throw into sewer. If swallowed, seek medical advice immediately and show the container or label. Use only in well ventilated areas.