

## Fibre glass mesh

### Product Description

60 gr and 132 gr/m<sup>2</sup> fibreglass mesh

### Consumption

Consumption is 60 gr or 132 gr/m<sup>2</sup>

### Uses

- Under the basement and terrace waterproofing membranes,
- In liquid waterproofing membrane applications, it is used to increase flexibility and strength between floors.

### Advantages

- Stays permanently elastic after curing,
- Remains flexible in low and high temperatures,
- Resistant to temperature extremes,
- Resistance to aging, cracking and discoloring,

### Packing

BILIZO<sup>®</sup> MESH is packed in 200-meter rolls.

## Technical Data

<b>Material Structure</b>	Fibreglass mesh
<b>Color</b>	White
<b>Characteristic</b>	4mm x 4mm / 132gr/m <sup>2</sup>
<b>Warp Yarn</b>	134 tex x 2
<b>Weaving</b>	300 tex
<b>Dimension</b>	4 mm x 4 mm
<b>Average Weight</b>	132 gr/m <sup>2</sup> +3 gr/m <sup>2</sup>
<b>Width</b>	1000 mm
<b>Length</b>	200 m
<b>Stress Coefficient</b>	
Warp Yarn	1387 N/50mm
Weaving	1460 N/50mm