

## MMA Acrylic Floor Paint

### Product Definition

BILIZO<sup>®</sup> MMA LINE is MMA acrylic resin-based, one-component, solvent-based floor, wall and work safety marking paint.

### Uses

It is used in workshops, playgrounds, multi-purpose concrete surface sports fields.

### Advantages

It is a solvent-based top coat paint that is applied cold, dries quickly even when applied thickly, is resistant to weather conditions, UV, has excellent abrasion resistance, does not turn yellow, is not affected by oil, diesel, does not change color on asphalt and concrete.

### Packaging

It is packaged as 22 kg net in 1 bucket. It is produced in white, yellow, red, black or desired colors.

### Technical Data

Connector Type	MMA Acrylic Resin
Viscosity(25°C, KU)	77-82
Density (g/ml)	1.37 ± 0.05
Solids (% by Weight)	68 ± 2
Covering Power	Min 90 (Yellow) Min 95 (White)
Storage Stability	Min 6 points
Drying Time (23°C, 50%RR)	Touch Dry : Max.15 minutes Full Drying : 45-60 minutes

### Application

#### Surface Preparation:

The surfaces to be applied must be free of oil, dirt and moisture.

#### Method of Application:

Depending on the application method and air temperature; it is applied as a single layer with roller, brush or painting machines. If a second coat application is required, wait at least 2 hours between coats.

#### Important Warnings:

Paint should be mixed well before use. During the application, the ambient temperature should be 5-35°C. After each application; application tools should be cleaned with cellulosic thinner. The surfaces on which MMA acrylic floor paint is applied should be protected from physical and chemical factors for 3-4 hours. Paint should never be discharged into sewers and water channels. The application should be done as stated above. After partial use; the mouth of the package should be tightly closed.

### Storage Conditions

It can be stored for one year in its unopened original packaging, in an environment of 5-35°C, out of direct sunlight. It should be protected from extreme temperature and humidity.

### Safety Information

This application is purely for professional users. Easily flammable. Harmful by inhalation, in contact with skin and if swallowed. Keep out of reach of children. Keep the box tightly closed, in a cool and well-ventilated place. Keep away from ignition sources, do not smoke. Avoid eye and skin contact. Do not throw into sewer. If swallowed, seek medical advice immediately and show the container or label. Use only in well ventilated areas.