

# **BILIZO**<sup>®</sup> **TOPCOAT MMA**

## **Sports Field Floor Paint (UV resistant)**

### **Product Definition**

MMA acrylic resin-based, one-component, solvent-based floor and wall paint.

### **Advantages**

It is a solvent-based top coat paint that is applied cold, dries quickly even when applied thickly, is resistant to weather conditions, UV, has excellent abrasion resistance, does not turn yellow, is not affected by oil, diesel, does not change color on asphalt and concrete.

### **Uses**

Workshops, playgrounds, multi-purpose concrete surface sports fields.

### **Packaging**

BILIZO<sup>®</sup> TOPCOAT MMA is packaged in 20 kg pails.

### **Technical Data**

<b>Connector Type</b>	MMA acrylic resin	
<b>Viscosity (25°C, KU)</b>	77-82	
<b>Density (g/ml)(23 °C)</b>	1.37 ± 0.05	
<b>Solids (% by Weight)</b>	68 ± 2	
<b>Drying Time (23°C, 50%RR)</b>	Touch Dry	Max 20 - 30 minutes
	Full Dry	24 hours

### **Application**

#### **Surface Preparation**

The surfaces to be applied must be free of oil, dirt, dust and moisture.

#### **Method of Application**

Depending on the application method and air temperature; it is applied as a single layer with roller, brush or painting machines. If a second coat is required, wait at least 2 hours between coats.

#### **Important Notices**

Paint should be mixed well before use. During the application, the ambient temperature should be 5-35°C. After each application; application tools should be cleaned with cellulosic thinner. BILIZO<sup>®</sup> MMA acrylic floor paint applied surfaces should be protected from physical and chemical factors for 3-4 hours. Paint should never be discharged into sewers and water channels. The application should be done as stated above. After partial use; the mouth of the package should be tightly closed.

### **Storage Conditions**

It can be stored for one year in its unopened original packaging, in an environment of 5-35°C, out of direct sunlight. It should be protected from extreme temperature and humidity.

### **Safety Information**

Easily flammable. Harmful by inhalation, in contact with skin and if swallowed. Keep out of reach of children. Keep the box tightly closed, in a cool and well-ventilated place. Keep away from ignition sources, do not smoke. Avoid eye and skin contact. Do not throw into sewer. If swallowed, seek medical advice immediately and show the container or label. Use only in well ventilated areas.

Note: This paint is purely for professional users. This information has been prepared based on laboratory experiments and research under normal conditions. Our company is not responsible for applications made under inappropriate conditions.